



**ARDON®**  
**WORKWEAR**  
& **OUTDOOR**

## ARDON® AUGUST

HANDLING IN DRY ENVIRONMENT WITH MECHANICAL PROTECTION AND HEAT PROTECTION



EN 388: 2016



EN 407:2020

TECHNICAL DATA



**ARDON®**  
**WORKWEAR**  
& OUTDOOR

# ARDON® AUGUST

HANDLING IN DRY ENVIRONMENT WITH MECHANICAL PROTECTION AND HEAT PROTECTION

## CODE

**A1077**

## MATERIAL

Palm  
Back  
Cuff  
Thickness

reversed goatskin (brown)  
polyester (blue)  
rubber + Velcro  
4,1 mm (in palm)

## SIZE(S)

6 / XS – 11 / 2XL

## UNIT

pair

## PACKING

Units in carton  
Units in polybag  
Retail packaging


60 pairs  
12 pairs  
sales label

## DIMENSIONS

|                       | 5 | 6        | 7        | 8        | 9        | 10       | 11       | 12 |
|-----------------------|---|----------|----------|----------|----------|----------|----------|----|
| Carton H x W x D (cm) | - | 45x26x37 | 45x27x38 | 45x27x38 | 44x29x40 | 44x29x40 | 44x29x43 | -  |
| Carton (cbm)          | - | 0,0433   | 0,0462   | 0,0462   | 0,0510   | 0,0510   | 0,0549   | -  |

## WEIGHT

|             | 5 | 6     | 7     | 8     | 9     | 10    | 11    | 12 |
|-------------|---|-------|-------|-------|-------|-------|-------|----|
| Carton (kg) | - | 6,750 | 7,250 | 7,750 | 8,520 | 8,600 | 9,640 | -  |
| Unit (g)    | - | 112,2 | 120,0 | 129,0 | 142,0 | 143,0 | 160,0 | -  |



## Size chart (cm)

|                  | 5 | 6    | 7    | 8    | 9    | 10   | 11   | 12 |
|------------------|---|------|------|------|------|------|------|----|
| Total length (A) | - | 21,0 | 22,0 | 23,0 | 24,0 | 25,0 | 26,0 | -  |
| Cuff length (B)  | - | 4,00 | 4,00 | 4,00 | 4,00 | 4,00 | 4,00 | -  |
| Cuff width (C)   | - | 6,50 | 7,50 | 8,50 | 9,50 | 10,5 | 11,5 | -  |
| Palm width (D)   | - | 10,0 | 10,5 | 11,0 | 11,5 | 12,0 | 12,5 | -  |

Tolerance (A) ± 0,3 (cm)

Tolerance (B) ± 0,3 (cm)

Tolerance (C) ± 0,3 (cm)

Tolerance (D) ± 0,3 (cm)

## DESCRIPTION

Reversed goatskin leather gloves with polyester back and Velcro cuff.

TECHNICAL DATA



**ARDON®**  
**WORKWEAR**  
& OUTDOOR

## STANDARDS

(EU) 2016/425

**EN ISO 21420:2020** Protective gloves – general requirements and test methods

**EN 388:2016 + A1:2018** Protective gloves against mechanical risks

| PROTECTION LEVELS                                                                 |        |                            |     |               |        |
|-----------------------------------------------------------------------------------|--------|----------------------------|-----|---------------|--------|
|  | EN 388 | MECHANICAL RISKS           | LVL | score         | unit   |
|                                                                                   |        | abrasion resistance        | 3   | 2.000 – 8.000 | cycles |
|                                                                                   |        | cut resistance             | 1   | 1,2 – 2,5     | index  |
|                                                                                   |        | tearing resistance         | 1   | 10 – 25       | N      |
|                                                                                   |        | puncture resistance        | 3   | 100 – 150     | N      |
|                                                                                   |        | cut resistance acc. to ISO | X   | not measured  | N      |

**EN 407:2020**

Protective gloves against heat or flame

| PROTECTION LEVELS                                                                   |                                            |       |
|-------------------------------------------------------------------------------------|--------------------------------------------|-------|
| EN 407                                                                              | THERMAL RISKS                              | score |
|  | resistance to burning                      | X     |
|                                                                                     | resistance to contact heat                 | 1     |
|                                                                                     | resistance to convective heat              | X     |
|                                                                                     | resistance to radiant heat                 | X     |
|                                                                                     | resistance to small drops of molten metals | X     |
|                                                                                     | resistance to large drops of molten metals | X     |
|                                                                                     |                                            |       |

### SPECIAL FEATURES

- ARDON® design:
  - mandatory information on inner label
  - manufacturer's logo on the back
- equipped with an adjustable velcro cuff thanks to which they do not slip out of the hand or move
- the padding in the palm eliminates calluses and slightly dampens vibrations
- wide size range retail ready
- EN 407:2020 valid from 04/2024
- heat protection up to 100 °C
- available also in fingerless version (code A1080)



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

**Retail packaging (with sales label)**

A1077/06-SPE  
A1077/07-SPE  
A1077/08-SPE  
A1077/09-SPE  
A1077/10-SPE  
A1077/11-SPE

**EAN**

8592390039149  
8592390077431  
8592390041692  
8592390081872  
8592390041715  
8592390011367



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

