



ARDON®
WORKWEAR
& OUTDOOR

BRAD

HANDLING IN LIGHT OILY ENVIRONMENT



EN 388: 2016

TECHNICAL DATA



ARDON
WORKWEAR
& OUTDOOR

BRAD

HANDLING IN LIGHT OILY ENVIRONMENT

CODE

A5016

MATERIAL

Lining 13G polyester (white)
Coating nitrile (grey)
Thickness 1,0 mm (in palm)

SIZE(S):

6 / XS – 11 / 2XL

UNIT

pair

PACKING

Units in carton 240 pairs
Units in polybag 12 pairs
Retail packaging N/A

DIMENSIONS


Carton H x W x D (cm)
Carton (cbm)

5	6	7	8	9	10	11	12
-	50x25x44	50x25x44	50x25x44	50x25x44	50x25x44	50x25x44	-
-	0,055	0,055	0,055	0,055	0,055	0,055	-

WEIGHT

Carton (kg)
Unit (g)

5	6	7	8	9	10	11	12
-	9,10	9,40	9,60	11,3	11,8	12,1	-
-	37,9	39,2	40,0	47,1	49,2	50,4	-



Size chart (cm)

Total length (A)
Cuff length (B)
Cuff width (C)
Palm width (D)

5	6	7	8	9	10	11	12
-	22,0	23,0	24,0	25,0	26,0	27,0	-
-	6,80	7,00	7,50	7,70	8,00	8,20	-
-	7,50	8,00	8,20	8,20	8,20	8,50	-
-	8,50	9,00	9,50	10,0	10,5	11,0	-

Tolerance (A) $\pm 0,50$ (cm)
Tolerance (B) $\pm 0,30$ (cm)

Tolerance (C) $\pm 0,30$ (cm)
Tolerance (D) $\pm 0,30$ (cm)

DESCRIPTION

Polyester knit dipped in nitrile.

TECHNICAL DATA

**ARDON®****WORKWEAR
& OUTDOOR**

STANDARDS

(EU) 2016/425**EN ISO 21420:2020** Protective gloves – general requirements and test methods**EN 388:2016 + A1:2018** Protective gloves against mechanical risks**EN 388****PROTECTION LEVELS****MECHANICAL RISKS**

abrasion resistance
cut resistance
tearing resistance
puncture resistance
cut resistance acc. to ISO

LVL

2
1
2
X
X

score

500 – 2.000
1,2 – 2,5
25 – 50
not measured
not measured

unit

cycles
index
N
N
N

SPECIAL FEATURES

- dipping with non-slip finish

TECHNICAL DATA



ARDON®
WORKWEAR
& **OUTDOOR**

Basic packaging (without sales label)

A5016/06
A5016/7
A5016/08
A5016/09
A5016/10
A5016/11

EAN

8592390012456
8592390012463
8592390012470
8592390012487
8592390012494
8592390010995

HEM COLOR

purple
red
yellow
brown
black
green

TECHNICAL DATA